Manual Lifting Rotary Evaporator LX2001MRE

Email: info@labdex.com **website:** www.labdex.com

Description

Manual Lifting Rotary Evaporator LX2001MRE is a compact and upgraded rotary evaporator constructed from durable Borosilicate Glass 3.3 and features a 3 L evaporating flask along with a double vertical condenser for efficient vapour condensation. The unit includes electronic speed control for precise operation and is equipped with a weight-balanced manual lift (100 mm travel) and an auxiliary extension (150 mm) for flexible height adjustment.

Specifications

Rotary bottle volume	Pyriform 3 L
Receiving bottle volume	Ball-shaped 2 L
Rotational speed	20 - 120 rpm
Material	Borosilicate glass 3.3
Condenser	Double vertical
Controller	Electronic speed control
Heating bath power	1.3 KW
Temperature control range	Indoor temperature + 5 °C - 180 °C
Temperature regulation accuracy	Water ± 1 °C, Oil ± 2 °C
Lifting method	Weight-balanced 100 mm with auxiliary extension 150 mm
Voltage	AC 220 V, 50 Hz
External dimension	510 x 380 x 750 mm
Packing dimension	510 x 380 x 750 mm
Gross weight	17 Kg

Features

- Constructed with high-quality Borosilicate Glass 3.3
- It has ball-shaped receiving bottle with 2 L volume
- Integrated with a rotational speed regulator and temperature control device
- Digital display for clear visualization of rotational speed

- Temperature regulation accuracy: ±1 °C for water and ±2 °C for oil baths
- Equipped with a control panel and power switch
- Includes a manual lifting handle
- Fitted with a double vertical condenser

Applications

- It is ideal for routine solvent evaporation and distillation tasks in academic, research, and quality control laboratories, where precise temperature and speed control are essential for consistent performance.

Optional Accessories

- Chiller
- Vacuum pump

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.
Email: info@labdex.com | Website: www.labdex.com